

## AXIS M2026-LE Mk II Network Camera

Affordable, outdoor-ready camera with 4 MP and built-in IR

AXIS M2026-LE Mk II is a small, bullet-style camera delivering high-quality images in 4 MP resolution. The camera has built-in IR illumination that enables surveillance up to 15 m even at nighttime. The outdoor-ready camera is resistant to rough weather and the integrated sunshield protects against sun and rain. With a 130° field of view, a single camera gives full surveillance at low cost, and Axis Corridor Format provides efficient monitoring of corridors and shopping aisles. With Axis Zipstream technology storage and bandwidth requirements are significantly reduced and the camera supports video compression in both H.264 and H.265.

- > **Outdoor-ready, IP66- and NEMA 4X-rated**
- > **4 MP / Quad HD 1440p**
- > **Built-in IR illumination**
- > **130° field of view**
- > **Zipstream and H.265 video compression**



# AXIS M2026-LE Mk II Network Camera

|  |  |  |
|--|--|--|
| <b>Models</b>                            | AXIS M2026-LE Mk II<br>AXIS M2026-LE Mk II Black   | AXIS Video Motion Detection, active tampering alarm<br><b>Supported</b><br>AXIS Digital Autotracking, AXIS Cross Line Detection<br>Support for AXIS Camera Application Platform enabling<br>installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a> |
| <b>Camera</b>                            |  |  |
| <b>Image sensor</b>                      | 1/3" progressive scan RGB CMOS   |  |
| <b>Lens</b>                              | M12 mount, Fixed iris, Fixed focus<br>2.4 mm, F2.2<br>Horizontal field of view: 130°<br>Vertical field of view: 73°  |  |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter  |  |
| <b>Minimum illumination</b>              | Color: 0.3 lux at 50 IRE, F2.2<br>B/W: 0.06 lux at 50 IRE, F2.2<br>0 lux with IR illumination on   |  |
| <b>Shutter speed</b>                     | 1/31500 s to 1/5 s   |  |
| <b>Video</b>                             |  |  |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Main and High Profiles<br>H.265 (MPEG-H Part 2)<br>Motion JPEG  |  |
| <b>Resolution</b>                        | 2688x1520 to 320x240   |  |
| <b>Frame rate</b>                        | Up to 25/30 fps with power line frequency 50/60 Hz   |  |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG<br>Axis Zipstream technology in H.264 and H.265<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264/H.265  |  |
| <b>Multi-view streaming</b>              | Up to 2 individually cropped out view areas in full frame rate   |  |
| <b>Image settings</b>                    | Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR, rotation: 0°, 90°, 180°, 270° including Corridor Format, text and image overlay, privacy masks, mirroring of images   |  |
| <b>Pan/Tilt/Zoom</b>                     | Digital PTZ  |  |
| <b>Network</b>                           |  |  |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware   |  |
| <b>Supported protocols</b>               | IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, MQTT v3.1.1  |  |
| <b>System integration</b>                |  |  |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T. Specifications at <a href="http://onvif.org">onvif.org</a>  |  |
| <b>Event triggers</b>                    | Analytics, edge storage events   |  |
| <b>Event actions</b>                     | Record video: SD card and network share<br>Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email<br>Pre- and post-alarm video or image buffering for recording or upload<br>Notification: email, HTTP, HTTPS, TCP and SNMP trap<br>Overlay text   |  |
| <b>Data streaming</b>                    | Event data   |  |
| <b>Built-in installation aids</b>        | Pixel counter  |  |
| <b>Analytics</b>                         |  |  |
| <b>Applications</b>                      | Included<br>AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard  |  |
| <b>General</b>                           |  |  |
| <b>Casing</b>                            | IP66-, NEMA 250 Type 4X-, and IK08-rated, polymer casing<br>Encapsulated electronics, captive screws (Torx <sup>®</sup> 10)<br>M2026-LE Mk II: Color: White NCS S 1002-B<br>M2026-LE Mk II Black: Color: Black NCS S 9000-N  |  |
| <b>Sustainability</b>                    | PVC free   |  |
| <b>Memory</b>                            | 512 MB RAM, 256 MB Flash   |  |
| <b>Power</b>                             | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3<br>Typical 5.1 W, max 7.9 W  |  |
| <b>Connectors</b>                        | RJ45 10BASE-T/100BASE-TX PoE   |  |
| <b>IR illumination</b>                   | Power-efficient, long-life 850 nm IR LEDs. Range of reach up to 15 m (50 ft) depending on scene  |  |
| <b>Storage</b>                           | Support for microSD/microSDHC/microSDXC card<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>  |  |
| <b>Operating conditions</b>              | -30 °C to 50 °C (-22 °F to 122 °F)<br>Humidity 10–100% RH (condensing)   |  |
| <b>Storage conditions</b>                | -40 °C to 65 °C (-40 °F to 149 °F)<br>Humidity 5–95% RH (non-condensing)   |  |
| <b>Approvals</b>                         | EMC<br>EN 55032 Class A, EN 55024, IEC 62471, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35<br>Environment<br>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-78, IEC 60068-2-14, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250 Type 4X<br>Safety<br>IEC/EN/UL 62368-1, IS 13252<br>IEC/EN/UL 60950-22<br>Network<br>NIST SP500-267 |  |
| <b>Dimensions</b>                        | Height, straight: 174 mm (6.9 in)<br>Height, angled: 118 mm (4.6 in)<br>ø 101 mm (4.0 in)  |  |
| <b>Weight</b>                            | 0.5 kg (1.1 lb)  |  |
| <b>Included accessories</b>              | Installation Guide, Windows <sup>®</sup> decoder 1-user license, Torx <sup>®</sup> L-key, Connector guard  |  |
| <b>Optional accessories</b>              | AXIS T94B03L Recessed Mount, AXIS T94B02D Pendant kit, AXIS T94B01P Conduit Back Box, AXIS T94B02M J-Box/Gang Box Plate, Axis mounts, AXIS Surveillance microSDXC™ Card<br>AXIS T94 mounts for various installations<br>For more accessories, see <a href="http://axis.com/vms">axis.com/vms</a>   |  |
| <b>Video management software</b>         | AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>   |  |
| <b>Languages</b>                         | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese  |  |
| <b>Warranty</b>                          | 5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>  |  |

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](http://www.openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)